

# H D B 096 G 1 2 2 4 2 X X X

**PRODUCT PROFILE**

S = 3.5" x 4.5" STD  
 M = 3.5" x 4.5" MED  
 H = 3.5" x 4.5" HVY  
 I = 4" x 6"  
 X = 4" x 7.5"

**APPLICATION**

T = TANGENT  
 D = DEADEND  
 B = STACKED DOUBLE DEADEND  
 H = H-FRAME  
 A = ALLEY  
 Z = OTHER

**MOUNTING HARDWARE**

B = STANDARD BRACKET ASSEMBLY  
 N = NO MOUNTING HARDWARE  
 S = SIDE MOUNT BRACKET  
 Z = SPECIAL MOUNTING HARDWARE

**LENGTH IN INCHES**

036 = 3'	054 = 4'6"	072 = 6'
096 = 8'	120 = 10'	144 = 12'

**GUY ATTACHMENT**

G = DOUBLE GUY  
 N = NO GUY ATTACHMENT  
 B = BRACELESS ALLEY ARM

**GAIN HOLE SPACING FOR MOUNTING (inches)**

08 = 8" *	10 = 10" *
12 = 12"	ZZ = Other**

\*Guy attachment not available with less than 12" spacing  
 \*\*Contact factory

**WIRE POSITIONS**

2 = 2    4 = 4  
 6 = 6

**NUMBER OF EYENUTS**

2 = 2	8 = 8	C = 12	F = 15
4 = 4	A = 10	D = 13	G = 16
6 = 6	B = 11	E = 14	etc.

**COATING**

2 = GRAY  
 5 = DARK BRONZE  
 9 = CUSTOM COLOR\*

**SPECIAL DRILL PATTERN OR SPECIAL REQUIREMENTS**

XXX = UNIQUE DESIGNATION

© 2019 Shakespeare - Valmont Composite Structures. All rights reserved. Shakespeare has a policy of continuous product improvement and development. As a result, certain changes in standard equipment, options, price, etc., may have occurred after the publication of this document. Some images and specifications may not be identical to current production. Shakespeare reserves the right to change product design and specifications at any time without incurring obligations. Document updated 0619.