



Quick Flooring Guide

Choosing the right flooring

Load 2.5kPa/Deflection 5mm												
Span mm	Steel	Aluminium	FRP									
600 900 1200 1500 1800	C205MP C205MP C205MP A255MP A325MP	A253AP A253AP A255AP A403AP A503AP	G256 G386 G386									

Light occasional use. No public access - AS/NZS1657

Load 5kPa/Deflection 5mm												
Span mm	Steel	Aluminium	FRP									
600 900 1200 1500 1800 2100	C205MP C205MP C255MP A325MP A405MP A505MP	A253AP A253AP A325AP A503AP A503AP	G256 G386									

Heavy use. Occasional placement of heavy tools - AS/NZS1170

Load 3kPa/Deflection 5mm												
Span mm	Steel	Aluminium	FRP									
600 900	C205MP C205MP	A253AP A253AP	G256 G386									
1200	C205MP	A255AP										
1500	A255MP	A405AP										
1800	A325MP	A505AP										
2100	A405MP											

Light occasional use. No public access - AS/NZS1170

	Load 4kPa /	Doflaction Emm	Load 4/Da /Deflection Fmm												
Span mm	Steel	Aluminium	FRP												
(00	(20540	425240	63F /												
600	C205MP	A253AP	G256												
900	C205MP	A255AP	G386												
1200	F255MP	A325AP													
1500	F325MP	A405AP													
1800	C405MP	A505AP													
2100	C505MP														

Heavy frequent use. No public access - AS/NZS1170

Load 5kPa/Deflection 10mm												
Span mm	Steel	Aluminium	FRP									
600 900 1200 1500 1800 2100	C205MP C205MP C205MP A255MP A325MP C405MP	A253AP A253AP A255AP A403AP A503AP	G256 G386 G386									

Heavy use - Occasional placement of heavy tools - AS/NZS1170

Load 7.5kPa/Deflection 10mm												
Span mm	Steel	Aluminium	FRP									
600 900 1200 1500 1800 2100	A205MP A205MP A205MP C325MP A405MP C505MP	A253AP A255AP A325AP A405AP A505AP	G256 G386									
Heavy use. F	requent placeme	nt of heavy tools - AS	/NZS1170									

Note kPA: (Kilopascals): Expression of Uniformly Distributed Load.

Other combinations of pattern and load bar are available beyond those listed above. See load tables on page 6/7 for more detail.



Grating Patterns

STEEL







PATTERN B.

11111111		100mm —
FIIIII	I Bar Pitch	
THINN	Load 40mr	

PATTERN C.



PATTERN D.





* For confirmation of stock panel widths and load bar multiples, refer to the Webforge website.





PATTERN A.



PATTERN B.

- Cross Rod Pitch



PATTERN C.



PATTERN D.





Grating

Materials:

Mild Steel (M):

Recommended for high impact, high load applications where economy and strength are paramount.

Grating is manufactured from a minimum of Grade 250 Mild Steel (or equivalent).

Aluminium (A):

Recommended where light weight is important and where quality of appearance is paramount. Material 6063-T6

Stainless Steel (S):

Recommended where rust resistance or hygienic environment is required. ASTM A240 GR316.

Top Surface:

Standard grating comprises Plain (P) square edge flat bars. To increase the slip resistance, Serrated (S) grating can be specified. Stainless Steel, 6mm bars, and any load bars 20mm deep will not be serrated.

In addition, both steel and aluminium grating can improve their slip resistance by setting the load bars parallel to the walking direction over the floor. In steel grating better slip resistance is available in patterns with 100mm cross rod centres, ie Patterns A & C.

As mandated by AS/NZS1657, the use of 10 x 10mm square bar cleats must be used for additional security on slopes >10. ISO14122.1 recommends cleats between 10° and 20°.

Treatment/Colour: (Conditions apply)

Mild Steel Grating

- Galvanised (G) (AS/NZS 4680)
- Untreated (Ù)

Stainless Steel Grating

- Mill Finish (M)
- Electropolished (E)
 Passivated (P)

Aluminium Grating

- Anodised (A)
- Powder Coated (PC)
 Painted (P)
- Mill finish (M)

* For FRP Grating info refer to p8.

Aluminum Grating Code Example



Stainless Steel Grating Code Example



Steel Grating Code Example



Standard Panel Sizes:

Mild Steel Grating

The standard range of panel sizes are;

Code Panel Sizes nominal

1000 x 5800 span
 1200 x 5800 span *sourced from WA

Panels can be cut and fabricated to order.

Aluminium Grating

The standard range of Aluminium panel size:

Code Panel Sizes nominal

12 1000 x 5800 span

6m panels available on request.

Custom panels can be manufactured in load bar multiples up to 1200mm wide.

Stainless Steel Grating

As dictated by the availability of raw material flat bar, usually 4000mm span. Please enquire at branch.

Panel sizes are nominal. Dimensions will vary slightly according to load bar thickness and the pattern.

Span Direction

- The direction that the load bars run, is known as the Span, and is important when considering supporting the grating.
- Span is always the last dimension given when referencing a panel size
- Grating has to be supported 90° to the span direction and does not require support on the other sides.

Load Bar Direction

The load bar is the flat bar from which the grating is made and the support of the support of the grating has to be perpendicular to this direction. The direction of the load bar defines the span of the grating.

Considerations when choosing Stock Panels

- Utilise the Quick Flooring Guide to choose the most appropriate combination of Pattern and Load Bar, for your application.
- Add codes for options; Material, Top Surface, Treatment/Colour
- Select a standard panel size or provide details of custom sizes (see below)

Considerations when choosing Custom Panels

- Utilise the Quick Flooring Guide to choose the most appropriate combination of Pattern and Load Bar, for your application.
- Add codes for options; Material, Top Surface, Treatment/Colour
- Do you need panels to be 'Banded' or 'Cut to Size' only.
 See website for terminology
- Panel sizes are specified in Width & Span (Span is always the last dimension)
- Webforge will supply panels optimised to the maximum length unless notified otherwise.
- As standard, Webforge wont match cross rods.

*NB. Panel widths should be in load bar multiples. See p15 for details

Considerations for large projects or floor areas

- Webforge can provide a detailed quotation for large areas, based on detailed drawings of the area, including;
 - Dimensions
 - Span
 - Section size, location of and toe direction of the support steel
 - Location and size of cut outs and removable areas
 - Location of kick plate and nosings
 - · Indicate if penetrations are required to be split



CORRECT

INCORRECT



Steel Load Table

E

Span

ಕ	Bar Gi	Image: Second																		
Produ	Load	Loadh	Mass	4kPa		450	600	750	900	1050	1200	1350	1500	1800	2100	2400	2700	3000	3300	3600
F205MPU	20 x 5	60	19.8	1000	U (kPa) D (mm)	38.4	21.6	13.8	9.6 6.9	7.1	5.4 12.3	4.3	3.5	2.4						
C205MPU	20 x 5	40	23.3	1120	U (kPa)	56.5 1 7	31.8	20.3 4.8	14.1 6.9	10.4 9.4	7.9	6.3 15.5	5.1 19.2	3.5 27.6	2.6 37.5					
C253MPU	25 x 3	40 40	18.3 21.3	1170	U (kPa)	53.0	29.8	19.1	13.2	9.7	7.4	5.9	4.8	3.3	2.4					
F255MPU	25 x 5	60	23.2	1180	U (kPa)	60.0	33.8	21.6	15.0	11.0 7.5	8.4 9.8	6.7 12.4	5.4	3.8	2.8					
A205MPU	20 x 5	30	29.7	1190	U (kPa)	76.8	43.2	27.7	19.2	14.1 9.4	10.8	8.5	6.9	4.8	3.5	2.7 49.0				
C255MSU	25 x 5	40	27.4	1250	U (kPa) D (mm)	69.7 1.2	39.2 2.2	25.1 3.4	17.4 4.9	12.8 6.6	9.8	7.7	6.3 13.6	4.4	3.2 26.6	2.5				
A253MPU B253MPU	25 x 3 25 x 3	30 30	23.1 26.1	1250	U (kPa) D (mm)	72.0	40.5	25.9	18.0	13.2 7.5	10.1	8.0 12.4	6.5 15.3	4.5	3.3 30.0	2.5 39.2				
C255MPU	25 x 5	40	28.3	1320 1320	U (kPa)	88.3	49.7	31.8 3.8	22.1	16.2 7.5	12.4	9.8	7.9	5.5	4.1	3.1 39.2	2.5 49.6			
A255MSU	25 x 5	30	35.1	1330	U (kPa)	94.8	53.3	34.1 3.4	23.7	17.4	13.3 8.7	10.5	8.5 13.6	5.9	4.4	3.3 34.7	2.6 43.9			
F325MSU	32 x 5	60	27.3	1360	U (kPa)	81.6	45.9	29.4 2 7	20.4	15.0 5.3	11.5 6.9	9.1	7.3	5.1 15.6	3.7 21.2	2.9	2.3			
C323MPU	32 x 3	40	22.5	1400	U (kPa)	86.8	48.8	31.2 3.0	21.7 4.3	15.9 5.9	12.2	9.6 9.7	7.8	5.4	4.0	3.1 30.6	2.4			
A255MPU B255MPU	25 x 5 25 x 5	30 30	36.5 39.5	1410 1410	U (kPa)	120.0 1 4	67.5	43.2	30.0	22.0 7.5	16.9 9.8	13.3 12.4	10.8	7.5	5.5 30.0	4.2	3.3 49.6			
F325MPU	32 x 5	60	28.1	1420	U (kPa)	98.3 1 1	55.3 1.9	35.4 3.0	24.6 4.3	18.1 5.9	13.8	10.9	8.9 12.0	6.1 17.2	4.5	3.5 30.6	2.7	2.2 47.9		
A323MPU	32 x 3	30	28.8	1500	U (kPa) D (mm)	118.0 1.1	66.4 1.9	42.5 3.0	29.5 4.3	21.7 5.9	16.6 7.7	13.1 9.7	10.6	7.4	5.4 23.5	4.1 30.6	3.3 38.8	2.7 47.9		
C325MSU	32 x 5	40	34.4	1540	U (kPa) D (mm)	120.0	67.5 1.7	43.2	30.0 3.9	22.0 5.3	16.9 6.9	13.3 8.8	10.8 10.8	7.5	5.5 21.2	4.2	3.3 35.1	2.7 43.3		
C325MPU D325MPU	32 x 5 32 x 5	40 40	35.4 38.4	1580 1580	U (kPa) D (mm)	144.6 1.1	81.4 1.9	52.1 3.0	36.2 4.3	26.6 5.9	20.3 7.7	16.1 9.7	13.0 12.0	9.0 17.2	6.6 23.5	5.1 30.6	4.0 38.8	3.3 47.9		
A325MSU	32 x 5	30	44.5	1620	U (kPa) D (mm)	163.3 1.0	91.8 1.7	58.8 2.7	40.8 3.9	30.0 5.3	23.0 6.9	18.1 8.8	14.7 10.8	10.2 15.6	7.5 21.2	5.7 27.7	4.5 35.1	3.7 43.3		
C403MPU	40 x 3	40	27.4	1650	U (kPa) D (mm)	135.6 0.9	76.3 1.5	48.8 2.4	33.9 3.4	24.9 4.7	19.1 6.1	15.1 7.8	12.2 9.6	8.5 13.8	6.2 18.8	4.8 24.5	3.8 31.0	3.1 38.3		
F405MPU	40 x 5	60	33.6	1670	U (kPa) D (mm)	153.7 0.9	86.4 1.5	55.3 2.4	38.4 3.4	28.2 4.7	21.6 6.1	17.1 7.8	13.8 9.6	9.6 13.8	7.1 18.8	5.4 24.5	4.3 31.0	3.5 38.3		
A325MPU B325MPU	32 x 5 32 x 5	30 30	45.8 48.9	1680 1680	U (kPa) D (mm)	196.7 1.1	110.6 1.9	70.8 3.0	49.2 4.3	36.1 5.9	27.7 7.7	21.9 9.7	17.7 12.0	12.3 17.2	9.0 23.5	6.9 30.6	5.5 38.8	4.4 47.9		
A403MPU	40 x 3	30	35.2	1760	U (kPa)	184.4	103.7	66.4 2.4	46.1	33.9 4 7	25.9 6 1	20.5	16.6	11.5	8.5 18.8	6.5 24.5	5.1 31.0	4.1		
C405MPU	40 x 5	40	43.6	1860	U (kPa) D (mm)	226.0 0.9	127.1	81.4 2.4	56.5 3.4	41.5 4.7	31.8 6.1	25.1 7.8	20.3 9.6	14.1	10.4	7.9 24.5	6.3 31.0	5.1 38.3	4.2 46.3	3.5 55.2
A405MPU B405MPU	40 x 5	30 30	56.6	1980 1980	U (kPa)	307.3	172.9	110.6	76.8	56.4	43.2	34.1 7.8	27.7	19.2 13.8	14.1 18.8	10.8	8.5 31.0	6.9 38.3	5.7 46.3	4.8
C455MPU	45 x 5	40	48.7	2030	U (kPa)	286.0	160.9 1.4	103.0	71.5	52.5 4 2	40.2	31.8	25.7	17.9	13.1	10.1	7.9	6.4 34.0	5.3 41.2	4.5 49.0
A455MPU	45 x 5	30	63.3	2160	U (kPa)	389.0	218.8	140.0	97.2 3.1	71.4	54.7 5.4	43.2	35.0	24.3	17.9	13.7	10.8	8.8 34.0	7.2	6.1 49.0
C505MPU	50 x 5	40	53.7	2190	U (kPa)	353.1	198.6	127.1	88.3 2.8	4.2 64.9 3.8	49.7	39.2 6.2	31.8	22.1	16.2 15.0	12.4	9.8 24.8	7.9 30.6	6.6	5.5 44 1
A505MPU	50 x 5	30	70	2330	U (kPa)	480.2	270.1	172.9	120.0	88.2 3.8	4.5 67.5	53.4 6.2	43.2	30.0 11.0	22.0	16.9	13.3	10.8 30.6	8.9 37.1	7.5
A655MPU	65 x 5	30	90.2	2800	U (kPa)	811.5	456.5	292.2	202.9	3.8 149.1 2.0	4.9 114.1	90.2	73.0	50.7	37.3	28.5	22.5	18.3	15.1	12.7
A756MPU	75 x 6	30	123.6	3200	U (kPa)	1296.5	729.3	466.8	324.1	2.9	3.0 182.3	4.0	5.9 116.7	81.0	59.5	45.6	36.0	29.2	20.5	20.3

Spans in the darker shading (to the left of the heavy line) have a deflection of less than 5mm for a 4kPa uniformly distributed load. Mass shown is untreated and unbanded. Galvanising and banding will increase the mass as follows; A/B Pattern 12% nominal C/D Pattern 14% nominal F Pattern 16% nominal Load deflection tables are arranged in rising strength order. See the 4kPa, 5mm deflection column. U = Superimposed uniformly distributed load in kPa (100kg/m2 = 0.98kPa) D = deflection in mm for the load U Assumptions for load capacity is on single spans Based on allowable stress of 171 mPa for steel. Recommended minimum landing is equal to grating depth (minimum 25mm).



		u u u u u u u u u u u u u u u u u u u	acing mr	. /	^{uefi} Spa _l													
펄	Bar St		ka/m;		7						s	PAN mm						
The second secon	Lo ad	Load	Mass	4kpa		450	600	750	900	1050	1200	1350	1500	1800	2100	2400	2700	3000
F253APM	25 x 3	60	7	750	U (kPa) D (mm)	24.1 2.8	13.6 5.0	8.7 7.8	6.0 11.2	4.4 15.2	3.4 19.9	2.7 25.2	2.2 31.1	1.5 44.8	1.1 61.0	0.8 79.7	0.7 100.8	0.5 124.5
C253APM	25 x 3	40	7	890	U (kPa) D (mm)	35.5	20.0	12.8	8.9 11.2	6.5 15.2	5.0 19.9	3.9 25.2	3.2 31.1	2.2 44.8	1.6 61.0	1.2 79 7	1.0 100.8	0.8
A253ASM	25 x 3	30	8.4	900	U (kPa)	38.1	21.5	13.7	9.5	7.0	5.4	4.2	3.4	2.4	1.8	1.3	1.1	0.9
A253APM	25 x 3	30	8.7	950	U (kPa)	48.3	27.2	17.4	12.1	8.9 15.2	6.8	5.4	4.3	3.0	2.2	1.7	1.3	1.1
C255APM	25 x 5	40	10.5	1010	U (kPa)	59.2	33.3	21.3	14.8	10.9	8.3	6.6	5.3	3.7	2.7	2.1	1.6	124.5
A255ASM	25 x 5	30	12.8	1020	U (kPa)	63.6	35.8	22.9	15.9	11.7	8.9	7.1	5.7	44.0	2.9	2.2	1.8	124.5
C323APM	32 x 3	40	8.4	1070	U (kPa)	58.2	4.4 32.7	20.9	9.9	10.7	8.2	6.5	5.2	39.6	2.7	2.0	1.6	1.3
A255APM	25 x 5	30	13.3	1080	D (mm) U (kPa)	2.2 80.5	3.9 45.3	6.1 29.0	8.8 20.1	11.9 14.8	15.6 11.3	19.7 8.9	24.3 7.2	35.0 5.0	47.6 3.7	62.2 2.8	78.8 2.2	97.2 1.8
F403APM	40 x 3	60	9.2	1130	D (mm) U (kPa)	2.8 61.8	5.0 34.8	7.8 22.2	11.2 15.4	15.2 11.3	19.9 8.7	25.2 6.9	31.1 5.6	44.8 3.9	61.0 2.8	79.7 2.2	100.8 1.7	124.5 1.4
A323APM	32 x 3	30	10.6	1140	D (mm) U (kPa)	1.8 79.1	3.1 44.5	4.9 28.5	7.0 19.8	9.5 14.5	12.4 11.1	15.8 8.8	19.4 7.1	28.0 4.9	38.1 3.6	49.8 2.8	63.0 2.2	77.8 1.8
C325APM	32 x 5	40	12.9	1210	D (mm) U (kPa)	2.2 96.9	3.9 54.5	6.1 34.9	8.8 24.2	11.9 17.8	15.6 13.6	19.7 10.8	24.3 8.7	35.0 6.1	47.6 4.5	62.2 3.4	78.8 2.7	97.2 2.2
A325ASM	32 x 5	30	16	1240	D (mm) U (kPa)	2.2 109.4	3.9 61.5	6.1 39.4	8.8 27.4	11.9 20.1	15.6 15.4	19.7 12.2	24.3 9.8	35.0 6.8	47.6 5.0	62.2 3.8	78.8 3.0	97.2 2.5
CAOSADM	40 x 3	40	10.1	1260	D (mm)	2.0	3.5	5.5	7.9	10.8	14.1	17.8	22.0	31.7	43.1	56.3	71.3	88.0
0403AI W	40 x 5	40	10.1	1200	D (mm)	1.8	3.1	4.9	7.0	9.5	12.0	15.8	19.4	28.0	38.1	49.8	63.0	77.8
A325APIN	32 X 5	30	10.5	1300	D (KPa)	2.2	74.1 3.9	47.5 6.1	33.0 8.8	24.2	18.5	14.6 19.7	24.3	8.2 35.0	47.6	4.6 62.2	3.7 78.8	3.0 97.2
A403APM	40 x 3	30	12.8	1350	U (кРа) D (mm)	123.6 1.8	69.5 3.1	44.5 4.9	30.9 7.0	22.7 9.5	17.4 12.4	13.7 15.8	11.1 19.4	7.7 28.0	5.7 38.1	4.3 49.8	3.4 63.0	2.8 77.8
C405APM	40 x 5	40	15.7	1430	U (kPa) D (mm)	151.4 1.8	85.2 3.1	54.5 4.9	37.9 7.0	27.8 9.5	21.3 12.4	16.8 15.8	13.6 19.4	9.5 28.0	7.0 38.1	5.3 49.8	4.2 63.0	3.4 77.8
A405ASM	40 x 5	30	19.8	1480	U (kPa) D (mm)	179.2 1.6	100.8 2.9	64.5 4.5	44.8 6.5	32.9 8.9	25.2 11.6	19.9 14.7	16.1 18.1	11.2 26.1	8.2 35.5	6.3 46.3	5.0 58.7	4.0 72.4
C503APM	50 x 3	40	12.2	1490	U (kPa) D (mm)	142.0 1.4	79.9 2.5	51.1 3.9	35.5 5.6	26.1 7.6	20.0 10.0	15.8 12.6	12.8 15.6	8.9 22.4	6.5 30.5	5.0 39.8	3.9 50.4	3.2 62.2
A405APM	40 x 5	30	20.2	1530	U (kPa) D (mm)	206.0 1.8	115.9 3.1	74.1 4.9	51.5 7.0	37.8 9.5	29.0 12.4	22.9 15.8	18.5 19.4	12.9 28.0	9.5 38.1	7.2 49.8	5.7 63.0	4.6 77.8
C455APM	45 x 5	40	17.5	1560	U (kPa) D (mm)	191.7 1.6	107.8 2.8	69.0 4.3	47.9 6.2	35.2 8.5	27.0 11.1	21.3 14.0	17.3 17.3	12.0 24.9	8.8 33.9	6.7 44.3	5.3 56.0	4.3 69.1
A503APM	50 x 3	30	15.6	1600	U (kPa)	193.1	108.6	69.5 3.9	48.3	35.5	27.2	21.5	17.4	12.1 22.4	8.9 30.5	6.8 39.8	5.4 50.4	4.3
A455APM	45 x 5	30	22.6	1670	U (kPa)	260.7	146.6	93.8 4 3	65.2 6.2	47.9	36.7	29.0	23.5	16.3	12.0	9.2	7.2	5.9
C505APM	50 x 5	40	19.2	1690	U (kPa)	236.6	133.1	85.2	59.2	43.5	33.3	26.3	21.3	14.8	10.9	8.3	6.6	5.3
A505APM	50 x 5	30	24.9	1810	U (mm) U (kPa)	321.8	2.5	3.9 115.9	5.6 80.5	7.6 59.1	45.3	35.8	29.0	22.4	14.8	39.8 11.3	50.4 8.9	7.2
C655APM	65 x 5	40	24.5	2050	D (mm) U (kPa)	1.4 399.9	2.5 224.9	3.9 144.0	5.6 100.0	7.6 73.5	10.0 56.2	12.6 44.4	15.6 36.0	22.4 25.0	30.5 18.4	39.8 14.1	50.4 11.1	62.2 9.0
					D (mm)	1.1	1.9	3.0	4.3	5.9	7.7	9.7	12.0	17.2	23.5	30.6	38.8	47.9

Spans in the darker shading (to the left of the heavy line) have a deflection of less than 5mm for a 4kPa uniformly distributed load. Mass shown is untreated and unbanded. Banding will increase the mass as follows; A/B Pattern 10% nominal C/D Pattern 12% nominal F Pattern 14% nominal Load deflection tables are arranged in rising strength order. See the 4kPa, 5mm deflection column. U = Superimposed uniformly distributed load in kPa (100kg/m2 = 0.98kPa) D = deflection in mm for the load U Assumptions for load capacity is on single spans. Recommended minimum landing is equal to grating depth (minimum 25mm).

• Stainless Steel Load Table available from the website.



FRP Grating







*NB. Mini Mesh is only available in 38mm deep bars * Aperture is 12x 12mm

Features / Benefits

- Integral, one piece construction increases load-bearing capabilities
- Load applied to Webforge FRP bar is transferred to adjoining bearing bars, assisting in load distribution on the grating as well as on the support structure.
- Smooth resin-rich vertical surfaces and tapered bars allow all debris to fall through
- Continuous glass fibre strand in alternating layers thoroughly wetted with the appropriate resin for excellent corrosion resistance.

Material:

- Isopthalic Polyester Resin (I) ASTM E-84 Fire Rating Class A, 25 or less
- Vinyl Ester Rein (V) ASTM E-84 Fire Rating Class A, 25 or less

Top Surface:

FRP grating is provided with an antiskid Grit (G) surface as standard. This is a coarse grit that is embedded into the top surface of the grating. A plain top surface is available on request.

Treatment/Colour:

- Green (G) Isopthalic Polyester Resin or
- Yellow (Y) Vinyl Ester Resin
- Dark Grey (D) Mini Mesh only
- Others colours available on request

Panel Size:

The standard range of panel size is shown below:

Code Panel Size

1 1220 x 3660





FRP Load Table





FRP Grating

Webforge FRP Grating - Chemical Resistance Table

CHEMICAL ENVIRONMENT	% Concentration	°C TEMP	Vinyl Ester	Isophthalic		CHEMICAL ENVIRONMENT	% Concentration	°C TEMP	Vinyl Ester	Isophthalic
Acetic Acid	25	MAX	С	С		Lactic Acid	100	MAX	С	С
Acetic Acid	50	MAX	С	С	1 [Lithium Chloride (SAT)	SAT	MAX	Ν	Ν
Aluminum Hydroxide	ALL	MAX	С	С		Magnesium Chloride	ALL	MAX	С	С
Ammonium Chloride	ALL	48.8	С	С	1 [Magnesium Nitrate	ALL	MAX	С	С
Ammonium Bicarbonate	e 15	48.8	С	С		Magnesium Sulfate	ALL	MAX	С	С
Ammonium Bicarbonat	e 50	48.8	С	С	1 [Mercuric Chloride	ALL	MAX	C	С
Almmonium Hydroxide	20	26.6	S	Ν		Mercurous Chloride	ALL	MAX	С	С
Ammonium Sulfate	ALL	488	С	С	1 [Nickel Chloride	ALL	MAX	С	С
Benzene	100	65.5	I.	I		Nickel Sulfate	ALL	MAX	C	С
Benzoic Acid (SAT)	SAT	MAX	С	С	1 [Nitric Acid	20	48.8	S	S
Borax (SAT)	SAT	MAX	С	С		Oxalic Acid	ALL	65.5	C	С
Calcium Carbonate	ALL	MAX	С	С	1 [Perchloric Acid	30	32.2	S	
Calcium Nitrate	ALL	MAX	С	С		Phosphoric Acid	80	MAX	C	С
Carbon Tetrachloride	100	26.6	I	Ν	1 [Potassium Chloride	ALL	MAX	C	С
Chlorine, Dry Gas *	ALL	MAX	С	С		Potassium Dichromate	ALL	MAX	С	С
Chlorine Water (SAT)	SAT	48.8	С	l.	1 [Potassium Nitrate	ALL	MAX	С	С
Chromic Acid	50	65.5	I.	Ν		Potassium Sulfate	ALL	MAX	C	С
Citric Acid	ALL	MAX	С	С	1 [Propylene Glycol	ALL	MAX	C	С
Copper Chloride	ALL	MAX	С	С		Sodium Acetate	ALL	MAX	C	С
Copper Cyanide	ALL	60	С	S	1 [Sodium Bisulfate	ALL	26.6	S	S
Copper Nitrate	ALL	MAX	С	С		Sodium Bromide	ALL	26.6	C	С
Ethanol	10	488	С	S	1 [Sodium Cyanide	ALL	26.6	С	
Ethanol	50	488	С	1		Sodium Hydroxide	10	MAX	С	1
Ethylene Glycol	ALL	65.5	С	С	1 [Sodium Hydroxide	50	MAX	S	Ν
Ferric Chloride	100	MAX	С	С		Sodium Nitrate	ALL	MAX	С	С
Ferrous Chloride	ALL	MAX	С	С	1 [Sodium Sulfate	ALL	MAX	С	С
Formaldehyde 0-50%	50	48.8	S	I.		Sulfuric Acid	10	MAX	C	S
Gasoline	ALL	48.8	С	С	1 [Sulfuric Acid	25	MAX	С	S
Glucose	ALL	48.8	С	С		Sulfuric Acid	75	37.7	С	1
Glycerin	100	MAX	С	С] [Tartaric Acid	ALL	MAX	С	С
Hydrobromic Acid	50	MAX	S	S		Vinegar	ALL	MAX	C	С
Hydrochloric Acid	10	MAX	С	S] [Water, Distilled	ALL	MAX	С	С
Hydrochloric Acid	37	MAX	I.	S		Zinc Nitrite	100	MAX	С	С
Hydrogen Peroxide	30	26.6	С	Ν		Zinc Sulfate	100	MAX	С	С

C = Continuous exposure of the grating to the Chemical Environment listed at the temperature listed

S = *Frequent exposure of the grating to splashes and spills the Chemical Environment listed with that environment at the temperature listed I* = *Infrequent Exposure of the grating to splashes and spills from the Chemical Environment listed with that environment at the temperature*

listed and the spill immediately cleaned up or washed from the grating .

N = Not recommended for the concentrations and temperatures listed

T =Test

MAX = indicates temperature of 85°C for molded Vinyl Ester . 71°C for moulded Isopthalic grating.

ALL = All concentrations

SAT = Saturated solution



Stair Treads





FRP

AS1657 requires that the nosing of the tread is clearly visible against the background.



Bolted Fixing, Abrasive Nosing

Also available in Mini Mesh.



A **valmont 쯋** company

The tables below indicate the maximum width and length for stair treads, depending on the combination of material, pattern and load bar selected. Standard stair treads are available ex-stock from Webforge locations; these standard profiles are complimented by a custom manufacturing service.

Recommended Maximum Lengths for Grating Patterns														
		Steel			Aluminium	FRP								
Load Bar Size	25 x 5	32 x 5	40 x 5	25 x 5	32 x 5	40 x 5	25 x 6	38 x 6						
A & B Pattern	900	1300	1600	550	900	1275	-	-						
C & D Pattern	750	1200	1500	-	675	1050	-	-						
F Pattern	550	850	1350	-	450	700	-	-						
G Pattern	-	-	-	-	-	-	600	875						

Recommended Maximum Tread Widths for Grating Patterns														
A & B Pattern	125	155	185	215	245	275	305							
C & D Pattern	125	165	-	205	245	285	325							
F Pattern	125	-	185	-	245	-	305							
G Pattern	-	-	-	-	234	272	310							

End Plates

The standard tread end plates for the different width stair treads are shown below. Tread end plates are manufactured from 65 x 5 flat bar. For load bars > 40mm depth, special end plates are required.



125mm Tread Widths



25 **7** 50



205, 215, 245, 275, 285, 305 & 325mm Tread Widths

Tread Width

Note: All end plates sniped at 34° unless requested otherwise

Drilling Stringers:

Please find below a table of recommended stair stringer hole centres.

Table of recommended stair stringers drilling for M12 bolts				
Tread width mm	Recommended stringer hole centres mmHole size mm			
125	45	14 dia		
155, 165, 185	75	14 dia		
205, 215	100	14 dia		
245, 275, 285, 305, 325	125	14 dia		



Standard FRP Treads

Attach with: Top Saddle: C129SM Screw: C301SM 4 clips per tread (angle not supplied)



Minimesh Treads

Predrill angle with 7.4 Hole Attach with: Disc C140SM Top Saddle: C129SM Thread Rolling Screw: C309SM 4 clips per tread (angle not supplied)



Fixing Clips

	CLIP SET CODE	PATTERN	DESCRIPTION	COMPRISES	USAGE
Mild Steel	C001MG	A - F	Clip Set Mild steel Galvanised Top, Bottom & Bolt	Top clip C100MG Bottom C200MG M8 x 65mm Bolt C304MG	Mild Steel Grating Depth = <50mm Flange present
Aluminium	C0015M	A - F	Clip Set Stainless Steel Top, Bottom & Bolt	Top Clip C100SM Bottom C200SM M8 Bolt C301SM	Stainless Steel & Aluminium Grating Depth = <50mm Flange Present
Ł	C0305M	G	Clip Set Stainless Steel Top & Bolt	Top Clip C129SM M8 Bolt C301SM	FRP Grating Depth = 25mm & 38mm
FR	C0335M	Mini Mesh	Clip Set Mini Mesh Stainess Steel Top & Bolt	Top Disc C140SM M8 x 65mm Bolt C309SM	FRP Grating Depth = 38mm



Fixing Clips

Grating Bar depth* D (mm)

Min 20 Max 50

ø12

C140SM Discwasher

CLIP ASSEMBLIES





WELDING

Webforge believe that welding to the support structure is a suitable process. Minimum number of welds is four per panel. Grating: Weld 5mm fillet 25mm long at 1000mm centres.

CLIP FREQUENCY

Nominal 4 panel, or 4 per m², whichever is greater. (Approximately 3 per M² where span is >1500mm. Fixing clips are generally not recommended in areas of vibration or where lateral or cantilever loads are applied to the grating.



Manufacturing Tolerances



Installation Note:

Minimum support dimension:-

A minimum of 25mm for loadbars up to 50mm deep and a minimum of 50mm for loadbars > 50mm deep. Webforge recommends that the land on the support should be equal to the height of the load bar.

Grating Cantilevers:-

Grating cantilevers up to 250m in the loadbar direction are acceptable as long as the grating is securely anchored to the supports (not clips.) Cantilevers in the crossrod direction are not acceptable.

See website for terminoligy explanation.







Load Bar Chart

No. of b	AB oars	CD	F	G	
41	1205			1530	
40	1175			1492	
39	1145			1454	
38	1115			1416	
37	1085			1378	
36	1055			1339	
35	1025			1301	
34	995			1263	
33	965			1225	
32	935			1187	
31	905	1205		1149	
30	875	1165		1111	
29	845	1125		1073	
28	815	1085		1035	
27	785	1045		997	
26	755	1005		958	
25	725	965	920		
24	695	925	882		
23	665	885	844		
22	635	845		806	
21	605	805	1205	768	
20	575	765	1145	730	
19	545	725	1085	692	
18	515	685	1025	654	
17	485	645	965	616	
16	455	605	905	577	
15	425	565	845	539	
14	395	525	785	501	
13	365	485	725	463	
12	335	445	665	425	
11	305	405	605	387	
10	275	365	545	349	
9	245	325	485	311	
8	215	285	425	273	
7	185	245	365	235	
6	155	205	305	196	
5	125	165	245	158	
4	95	125	185	120	
3	65	85	125	82	
2	35	45	65	44	

WA	1205	1205	1205	
Other	995	1005	1025	

Note: Sizes are overall outside to outside of bars Calculations based on 5mm bars for A to F pattern. G pattern is FRP only. Bar centres are 38.1mm

Accessories

Webplate

Webplate is a flooring product that comprises floorplate welded to the top of the grating.

Any steel or aluminium grating pattern can be combined with any floorplate thickness. However Webforge recommends the use of Pattern F grating. Other combinations can be supplied on request.



Webplate is available in the following steel or aluminium combinations

Material	Product	Floor Treadplate Thickness	Grating	Weight Untreated Kg/sqm	Span at 4kPa UDL 5mm Deflection
STEEL	WP3 F255MP*	3mm	F255MP*	44.49	1390mm
	WP5 F325MP*	5mm	F325MP*	64.78	1625mm
ALUMINIUM	WP3 F255AP*	3mm	F255AP*	16.21	1100mm
	WP5 F325AP*	5mm	F325AP*	23.21	1350mm

Where *indicates treatment, refer to the website for a detailed description of part number protocols under steel and aluminium grating sections.

WebGrip[™] Anti-Slip

Available in:

- WebGrip[™] Anti-Slip Stair Nosing
- WebGrip[™] Metal Plating
- WebGrip[™] Metal Strips
- WebGrip[™] Conveyor Channel

Features:

- High Impact Resistance
- Anti-Slip Properties which overcome wet & oily surfaces
- Chermical & UV Resistance
- Durable Galvabond, Stainless Steel or Aluminium backing
- AS/NZ Certified

Stock sizes & Custom Manufactured sizes available

Webmesh

Webmesh comprises grating with a flattened, light gauge, expanded mesh welded to the underside to prevent tools and small objects from falling through the grating.

Meets the requirements of **AS/NZS1657 Clause 4.5** with mesh 1216F for steel grating or 1216AF for aluminium grating, welded to the underside of the grating.

* See website for more details.







Safety Barrier

Stanchion spacing dimensions must be nominated on the drawings. Stanchion type must be nominated. For stairways the stair angle and Hypotinuse (H) must be nominated. As per 'typical' drawings below. Safety barrier stanchions are seal welded to the rails.

	HANDRAIL	KNEERAIL
Steel	32NB	25NB
Aluminium	46 0.D. x 3.5mm	46 0.D x 3.5mm
Stainless Steel	32Sch10 2.8WT	32Sch10 2.8WT







Steel Stanchions



Steel Stanchions





Aluminium Stanchions







are 12 mm thick.

Aluminium Stanchions





Kickplate Mounting Brackets

55





Steel

DIMENSION 'D' FOR VARIOUS STANCHION TYPES					
DIMENSION 'D' FOR VARIOUS STANCHION TYPES					
Grating Height mm NIL 20,25,32 40,45,50 60, 65	;				
P, W, C D = 60 D = 85 D = 100 D = 12	0				
S & SO D = 135 D = 160 D = 180 D = 19.	5				

20mm GRATING



25mm GRATING



Stainless Steel & Aluminium

DIMENSION 'D' FOR VARIOUS STANCHION TYPES					
Grating Height mm	NIL	20,25,32	40,45,50	60, 65	
P, W, C	D = 40	D = 65	D = 80	D = 100	
S & SO	D = 115	D = 140	D = 160	D = 175	



TYPICAL KICKPLATE POSITIONS

Detail B

KICKPLATE MOUNTING BRACKET

KICKPLATE MOUNTING BRACKET NOTES

- 1. Kickplate mounting brackets are optional and must be specified when ordering.
- 2 Kickplate mounting brackets are mounted on the right hand side of the stanchion when viewed from the walking surface, unless DLSO.
- 3. The slot in the bracket allows for 7mm up/down adjusment of the kickplate.
- Standard kickplate is 100 x 6 flat but other 4. sizes are available.



Stainless Steel & Aluminium





P. S Stanchion **SO Stanchion**



A valmont 🌾 COMPANY

Closures Bends & Slip Joints





Gates

GATES - STEEL

Webforge Monowills gates are self - closing and are designed to be attached to Monowills stanchions. The direction or swing is critical to obtain a correctly functioning gate.

Webforge gates can be supplied with kickplate if required, or to suit the flatbar or structural styles at the top of a ladder. Single gates should not exceed 1200 mm; the most popular size is 800 mm.

Gates with kickplate should not exceed 1000mm maximum per gate.

GATES



- Spring Loaded
- Self Closing
- Padlock Option
- Combine with any stanchion
- Bracket variations for welding to columns

DIMENSION INSIDE STILES

- Double Gate
- Kickplate Optional







- - -9

Balustrades

Balustrade Barrier

Balustrades do not meet the dimensional requirements of AS/NZS1657

Notes:

To meet the requirements of AS/NZ51170 Table 3.3 C3 the stanchion spacing should not exceed 1.80m for the P units and 1.6m for S units. To meet the requirements of AS/NZ51428 a disability rail balustrade must be used with the attached handrail as shown. Balustrade barrier should not be more than 6.5m in length per panel. Avoid large right angle panels where the leg length exceed 2.5m for shipping and packing reasons. All balustrade must have fully sealed welded joints. * Not available in Aluminium



Special balustrade

Balustrade can be manufactured with different infill, eg. Expanded Metal, Woven Wire, Perforated Metal etc.

BAL-SP





Tolerances / Oneball Stanchions / Multi-ball



One Ball Stanchions

(Note these do not meet AS/NZS1428 or AS/NZS1657 requirements.) One ball stanchions are available with all the various stanchions configurations. These spheres are drilled for 32NB pipe UON.

The type of stanchion and the overall height have to be nominated. There are three handrail stanchion configurations as shown below: (Note these do not meet AS/NZS1428 handrail requirements due to the sphere.)

Drilled one side only

All stanchions can be provided in the drilled one side only; (DOSO) configuration. The conventions used are as shown and are nominated when viewed from the walking surface.

Multi Ball Stanchions

(Note these do not meet AS/NZS1657 requirements.)

Multi ball stanchions are available with all the various stanchions configurations. The drilling size to suit required rail pipe sizes and the spacing between spheres have to be nominated. Minimum sphere centres is 250mm. The type of stanchion and the overall height have to be nominated.

Preferred Drilling Dimensions

	Steel & Stainless steel	Aluminium
Toprail sphere	45mm	48mm
Kneerail sphere	36mm	48mm
Balustrade lower sphere	45mm	N/A

S Special Stanchion

The S special stanchion is available in the S, SAL, SAR and SC configurations. Please contact your Webforge branch.





Drilled Right Side Only



DBSO Drilled Bottom Side Only

Side Only

DTSO Drilled Top Side Only



Multi Ball

WEBFORGE

Sphere drilling

2 - 4 oversize

Jumbo Steel



Jumbo Steel

TOLERANCES



JUMBO RAIL BENDS (RB)



Stanchions tolerances

Height Angle drilling :+/- 1.5 degrees Base plate alignment :+/- 1 mm Vertical alignment Sphere drilling

: +/- 2.0 mm in 1 metre : +/- L / 100 : 2 - 4 oversize

CLOSURES & BENDS

Horizontal Closure Bends

Standard Pipe 65NB. med.



Angle Closure Bends (ACB)

Standard Pipe 65NB. med Available with ${f \alpha}$ value from 1° - 45°







A valmont 🌾 COMPANY

Jumbo Rails

JUMBO BALUSTRADE



JUMBO BALUSTRADE WITH DISABILITY HANDRAIL





JUMBO PANEL Showing Horizontal Closure Bend and End Caps

Jumbo stanchions Type JP. Handrail and kneerail 76.1mm 0.D.





Installation Details

Technical Details

Base Plate Fixings

Base plates for Standard monowills stanchions require 2-M-16 bolts. (17.5 holes.)

Base plates for Jumbo stanchions require 4-M-16 bolts. (20 holes.) When fixing into concrete, chemical anchors are required rather than expansion anchors.

Shims placed below the baseplate are acceptable for levelling the stanchion.

Rail fixings

All rails should preferably be jointed within the stanchion sphere. Where this is done then the slip joint can be omitted if the pipe is welded to the sphere. Where that is not possible the joint should occur in the outer quarters of the span between stanchions with a slip joint. Slip joints can be kept in position for steel stanchions with

- Welding
- Taper pins
- Screws

Sphere fixings

Rails should be fixed to spheres at least every 3m. by welding.

Closure bend fixings

Closure bends are welded to the top sphere and to the knee rail. The kneerail connection is either welded, pinned or screwed as the closure fits over the kneerail.

Expansion joints

In long runs of railings expansion joints are required. Expansion joints should be in the outside quarters of the span. Expansion joints are made by fixing one side of a slip joint and allowing the other side to be free.

Kickplate

Kickplate can be welded or bolted to the kickplate mounting bracket.

Stanchion spacings

Stanchions are spaced at nominally 2000mm maximum. Aluminium Stanchions are spaced at 1500mm maximum.



WEBFORGE

Aluminium

Installation Details

End caps

Monowills can be terminated with end caps This method is sometimes used when the handrail terminates at a wall or solid object. This is instead of an end closure. End caps are pressed onto the open pipe and must be placed once the pipe is through the stanchion spheres.

DOSO Stanchion

DOSO stands for drilled one side only and these stanchions are usually used against a wall or solid object or at a gate or ladder access point, replacing an end closure. Handrail should be installed working away from the DOSO stanchion.

Corner posts (PC)

A corner post stanchion can be used at 90 degree changes of direction instead of a 90 degree bend. Handrail should be installed working away from the corner stanchion. The handrail connection to the Corner post stanchion must be welded

Kickplate

Kickplate can be attached to the stanchions or be part of the flooring material. If a kickplate is required then the stanchions usually come with kickplate mounting brackets which are predrilled angles welded to the stanchion. Kickplate can be attached using M12 bolts in which case it needs to be drilled or it can be welded on site . The weld can be done on three sides of the angle or within the holes of the angle bracket.

In Ground Stanchions (IG, IGA)

In ground stanchions are supplied with an extra length leg to allow for casting into a footing. Footing sizes are as specified by the civil engineer.

Curved rails

Curved handrails are rolled to the radius specified. Curved rails should be erected as for straight runs but in some instances the stanchions will need to be placed loose on the rail before it is placed in position.

Balustrades

Balustrades are supplied in sections approximately 2m long. The end of one section fits into the stanchion on the next section. It is suggested that two sections are first erected as per Section 1 after which each section can be fitted.

The baseplates of balustrades need to be lifted over the fixing bolts. It is important the fixings are correctly spaced and extend sufficiently to protrude through the baseplate once fitted. Balustrades are joined as for rails.

Gates

Gates are manufactured with a swing direction. The gate stanchions are DOSO. Gate springs can be tensioned by turning the spring in the coil direction. Usually 2 to 3 turns are required.

More information can be found at www.webforge.com.au









Expansion Joint detail using a 150mm slip joint typ for top and knee rails Slip joint detail for a pipe join using a slip joint Typ for top and knee rails

WEBFORGE

Disclaimer: While Webforge has taken all reasonable care in preparing this brochure, Webforge takes no responsibility for loss resulting from relying on its contents. Customers should make their own enquiries as to whether any products described in this brochure are suitable for their intended use. Information in this brochure may change without notice. More information can be found at www.webforge.com.au

AUSTRALIA 1800 635 947 www.webforge.com.au wlcustomerservice@valmont.com NEW ZEALAND 0800 932 367 www.webforge.co.nz wlcustomerservice@valmont.com

