

TION 107 0 <th></th> <th></th> <th>1</th> <th></th> <th></th> <th></th>			1			
AVAILABLE TO SURFACE BELOW EATMENT FOR IN-SITU WELDS, CUT ENDS OR OTHER BARE AS/NZS 4680:2006 CLAUSE 8 REPAIR PROCEDURE. IT SYSTEMS TO BE IN ACCORDANCE WITH CLIENT OR AS CLIENT SPECIFIED. OGE/CULVERT CONCRETE TO BE GROUTED INTO Ø90mm HOLE IME AFTER THEY HAVE BEEN CAREFULLY ALIGNED. PEDESTRIAN BARRIER AND ARE NOT TO BE USED IN ES REQUIRE RESTRAINT. TEMS DO NOT COMPLY WITH AS1428.2 OT BE SUPPLIED IN ANGLE SCENARIOS OF 5 DEGREES OR LESS. (ISED 20/03/2023 AJM T CHANGED TO 900 FROM 1000 8/09/2022 AJM SECTION LETTERS REVISED 30/07/21 AJM ON 05/02/21 MDG SCRIPTION DATE DRAWN MDG CLIENT WEBFORGE PRODUCT MONOWILLS LINK DISABILITY 2 RAIL C/W KICK PLATE ASSEMBLY	IL TION		65 MAX			C
RED BARRIER SIZE - 32NB STANDARD SYSTEM OR 40NB HEAVY 2 THICK) GALVANISED STEEL TUBE. ED TO MATCH SHAPE OF PATH IF RADIUS IS LESS THAN 14m. TIONAL REQUIREMENTS OF AS/NZS 1428.1:2009 - DESIGN FOR ILITY 2 RAIL DESIGNED TO MEET BARRIER TYPE C3 AS/NZS ILITY 2 RAIL DESIGNED TO MEET BARRIER TYPE C3 AS/NZS ILITY 2 RAIL DESIGNED TO MEET BARRIER TYPE C3 AS/NZS ILITY 2 RAIL DESIGNED TO MEET BARRIER TYPE C3 AS/NZS ILIT OBE UNBROKEN & CONTINUOUS WITHOUT HAND UST EXTEND 300MM PARALLEL TO SURFACE BELOW EATMENT FOR IN-SITU WELDS, CUT ENDS OR OTHER BARE I AS/NZS 4680:2006 CLAUSE 8 REPAIR PROCEDURE. IT SYSTEMS TO BE IN ACCORDANCE WITH CLIENT IVE AS CLIENT SPECIFIED. IGE/CULVERT CONCRETE TO BE GROUTED INTO Ø90mm HOLE IME AFTER THEY HAVE BEEN CAREFULLY ALIGNED. IVE AFTER THEY HAVE BEEN CAREFULLY ALIGNED. IVE AFTER THEY HAVE BEEN CAREFULLY ALIGNED. IVE ASTRAINT. TEMS DO NOT COMPLY WITH AS1428.2 OT BE SUPPLIED IN ANGLE SCENARIOS OF 5 DEGREES OR LESS. TISED 20/03/2023 IVE ASTRAINS SECTION LETTERS REVISED 30/07/21 ON 05/02/21 MDG CLIENT WEBFORGE PRODUCT						
A A A A A A A A A A A A A A A A A A A	RED BARRIER SIZE - 32NB STANDARD SYSTEM OR 40NB HEAVY 2 THICK) GALVANISED STEEL TUBE. ED TO MATCH SHAPE OF PATH IF RADIUS IS LESS THAN 14m. TIONAL REQUIREMENTS OF AS/NZS 1428.1:2009 - DESIGN FOR ILITY 2 RAIL DESIGNED TO MEET BARRIER TYPE C3 AS/NZS IL TO BE UNBROKEN & CONTINUOUS WITHOUT HAND IUST EXTEND 300MM PARALLEL TO SURFACE BELOW EATMENT FOR IN-SITU WELDS, CUT ENDS OR OTHER BARE I AS/NZS 4680:2006 CLAUSE 8 REPAIR PROCEDURE. IT SYSTEMS TO BE IN ACCORDANCE WITH CLIENT OF AS CLIENT SPECIFIED. IGE/CULVERT CONCRETE TO BE GROUTED INTO Ø90mm HOLE IME AFTER THEY HAVE BEEN CAREFULLY ALIGNED. I PEDESTRIAN BARRIER AND ARE NOT TO BE USED IN					В
T CHANGED TO 900 FROM 1000 8/09/2022 AJM SECTION LETTERS REVISED 30/07/21 AJM ON 05/02/21 MDG SCRIPTION DATE DRAWN MDG CLIENT WEBFORGE 02DEC20 PRODUCT MONOWILLS LINK 02DEC20 DISABILITY 2 RAIL C/W KICK PLATE ASSEMBLY			OF 5 DEGREE	S OR LES	S.	
A A A A A A A A A A A A A A A A A A A			-			
ON 05/02/21 MDG SCRIPTION DATE DRAWN MDG 02DEC20 MT 02DEC20 DISABILITY 2 RAIL C/W KICK PLATE ASSEMBLY			-	_		
SCRIPTION DATE DRAWN MDG CLIENT WEBFORGE 02DEC20 PRODUCT MT MONOWILLS LINK 02DEC20 DISABILITY 2 RAIL C/W KICK PLATE				-		
MDG 02DEC20 MT 02DEC20 MT 02DEC20 CLIENT WEBFORGE PRODUCT MONOWILLS LINK DISABILITY 2 RAIL C/W KICK PLATE ASSEMBLY	-					
02DEC20 WEBFORGE PRODUCT MT 02DEC20 DISABILITY 2 RAIL C/W KICK PLATE ASSEMBLY		CLIENT		21010		A
MT MONOWILLS LINK 02DEC20 DISABILITY 2 RAIL C/W KICK PLATE ASSEMBLY	_					
02DEC20 DISABILITY 2 RAIL C/W KICK PLATE ASSEMBLY			ĸ			
ASSEMBLY		1		PLATE		
DRAWING NUMBER SHEET REV				, . , E		
	LOCKER		:	SHEET	REV	
COMPANY LKDS-EX-002 1 OF 1 3	COMPANY	LKDS-EX-002	<u>2</u>	1 OF 1	3	
			1	I_		