





Product Manual





www.ingalcivil.co.nz



Ingal MPR Motorcyclist Protection



1.0 Introduction

The Ingal Motorcyclist Protection Rail (Ingal MPR) is a protective enhancement installed on existing four-wheel vehicle restraint systems to reduce the chances of serious injury to motorcyclists and pillion passengers in run-off-road accidents.

Traditional highway safety barriers installed on the road carriageways to restrain vehicles from impacting roadside hazards, these typically take the form of the W-Beam rail supported by a series of posts. These posts introduce a significant hazard to an errant motorcyclist in a run-off-road accident. The Ingal MPR consists of an under-riding rail which is mounted on a spring bracket. Upon impacting this rail, the spring bracket deflects back absorbing some of the impact energy from the motorcyclist, whilst the rail contains and re-directs the motorcyclist away from the rigid posts and hazards.

The installer should ensure any variants of this product are approved by the final asset owner.

2.0 Specification

Ingal MPR Rail Length:	3.81m NLL
4m MPR Rail Mass:	12.3kg
Ingal MPR System Mass:	4.65kg per metre
Rail Height Above Ground:	60mm
Post Spacing:	2m or 3.81m
Ingal MPR Crash Test Impact Severity:	Level 1

The Ingal MPR rails and brackets are manufactured from hot-rolled steel flat products in accordance with AS/NZS1594. These items are hot dip galvanised in accordance with AS/NZS 4680 after fabrication leaving no surface untreated.

3.0 Crash Test Analysis

Crash test guidelines provide a minimum set of requirements that a roadside barrier has to meet in order to demonstrate its satisfactory impact performance. Whilst crash test guidelines cannot include all possible impact conditions that may be experienced in the real world, the crash test matrix is selected to represent a "worst practical condition" for a roadside barrier impact. The Ingal MPR system has been fully crash tested and evaluated according to Standards UNE 135900-1 and 2 and UNE EN-1317-1 and 2, and has produced satisfactory results in the following full scale crash tests. **The dummy tests recorded an impact severity of Level 1 which is the lowest severity for this testing standard.**

- TM1.6.0: Dummy to post, 60 km/h 30° angle of impact.
- TM.3.60: Dummy to point on barrier midway between posts, 60 km/h 30° angle of impact
- TB11:900 kg car at 100 km/h and 20° angle of impact.
- TB32: 1,500 kg car at 110 km/h and 20° angle of impact









4.0 Features and Benefits

- The specially designed anchoring system fully facilitates the positioning of the guard rail at the correct height, ensuring a uniform distance from the ground throughout the run and compensating for uneven terrain and height differences in the existing barriers. The mounting bracket also allows the motorcyclists rail to be raised to match alterations in the level of the road surface.
- The motorcyclist rail can be assembled and raised without the need to modify the traditional vehicle barrier system
- More space between the system and the ground (60mm), allowing water drainage, snow clearance, cleaning of hard shoulders, etc.
- The mounting bracket is symmetric, and is therefore the same for both the right and left side of the carriageway.
- Small number of components and ease of installation make the system very cost-effective.


5.0 Installation

The specially designed anchoring system facilitates the positioning of the guard rail at the correct height, allowing deflection of the system when impacted.

Only items provided by Ingal are to be used for the installation of the Ingal MPR. The following written instructions are to be read in conjunction with Ingal's drawings. A generic Safe Work Method Statement is available upon request for installation operations.

5.1 Site Preparation

This site should be prepared free of obstructing vegetation and other hazards that may interfere with the installation or operational performance of the system. Some sites may require minor grading if installed beyond the edge of the pavement shoulder.







Ingal MPR Motorcyclist Protection



5.2 Assembly

- Step 1 Assembly should be initiated with placing the post bracket around the guardrail posts, particular care should be taken to ensure the bracket is oriented in the correct direction with the open side facing the oncoming traffic for verge installations.
- Attach the rail bracket to the post bracket with Step 2 the M16 x 190 Hex Bolts. Typically the rail bracket will need to be abutting the underside of the block in the G4 guardrail system for convenient assembly. Tighten all fasteners to snug tight.
- Mount the rail on the rail brackets with the Step 3 appropriate fastener configuration. Before tightening, ensure a 60mm clearance between finished ground level and MPR rail.
- Terminate beginning and end of run with MPR Step 4 terminal piece.

5.3 **Curved Installations**


The MPR rails can be field curved down to a radius of 26m. Rails can be machine curved down to a radius of 5m. Contact your local Ingal office for details.



6.0 Product Storage

All posts and rails are hot dip galvanized in accordance with AS/NZS 4680. It is important that stored galvanized work is stacked so that each item is well ventilated and can adequately drain rainwater from its surfaces.

Poor storage can give rise to wet storage stain (white rust) which is caused by water (rain or condensation) in badly drained or ventilated conditions. This can occur very quickly, particularly in warm, humid conditions.





Ingal MPR Installation Checklist


Customer:	
Project:	
Barrier ID:	
Barrier Length:	
Checked By:	
Signed:	
Date	

Is the MPR rail ground clearance within tolerance of 60mm \pm 20mm	Yes	No
Has each end of the run been terminated with an MPR Terminal End	Yes	No
Have all fasteners been tightened to snug tight	Yes	No
Has a Ø70 x 2mm slot washer been used on the traffic side of the rail mounting	Yes	No
Has a Ø35 x 17 x 4mm washer been used on the verge side of the rail mounting	Yes	No
Has any minor damage been repaired using two coats of an organic zinc rich paint	Yes	No
Is the barrier system free from humps, sags or other irregularities	Yes	No
Are the barrier components free from splits, burrs or sharp edges after installation	Yes	No
Does the barrier form a smooth line vertically and horizontally when viewed along the run	Yes	No


Notes

Disclaimer:

Important Note: The conformity of the installation is the responsibility of the installation contractor, and Ingal Civil Products accepts no liability for or in connection with any installation that is outside of the specifications of this manual or the NZTA. For more information, please refer to our Standard Terms and Conditions of Sale available on our website: www.ingalcivil.co.nz.




03/21



Release 03/21

 \sim

	APPROACH-SIDE ELEVATION MEW			S	550 ()		100 100		2 2 10007777 MPR Tim 3 2 10006772 Rail mou 4 4 10001224 M16x240 5 4 10001248 Round hi 6 2 10006779 Round hi 7 2 10006771 Slot was 8 10 10006770 Washer 9 6 10007834 M16 nut	DESCRIPTION clist protection beam ber Post bracket nting bracket Hex Bolt & Nut ead bolt M16x32 ead bolt M16x40 sher Ø 70x2
	ELEVATION VIEW				1		 EVATION VIEW		PROJECT	
		1		NCES		DRAWN	DATE 7-10-2015	INGAL		INGAL CIVIL PRODUCTS PART No.
S				12						
SNOISIN				EREN.		CHECKED	7-10-2015 DRAWING AU	A valmont COMPANY		DRAWING No.
liul I	BON LIPOATED DESCRIPTION	MC	LG MC CHECKED APPROVED	REFERE	REFERENCE DRAWINGS		10-2015 DRAWING A		INGAL MPR MOTORCYCLIST PROTECTION	



Release 03/21

σ







Release 03/21







For more information

contact us on the web www.ingalcivil.co.nz

Auckland

12 Offenhauser Drive, East Tamaki, Auckland 2013, New Zealand Ph: 09 920 838 Email: sales@ingalcivil.co.nz Christchurch Ph: 0211 983 311 Wellington Ph: 021 504 870

Head Office: Sydney

57-65 Airds Road, Minto, NSW 2566 Ph: +61 2 9827 3333 Fax: +61 2 9827 3300 Free call (within Australia): 1800 803 795 Email: sales@ingalcivil.com.au