



Pallas, a range of conical lighting columns.


All shafts are manufactured from GL28h glued-laminated timber. The raw materials we use to produce our wooden columns are harvested from sustainability managed, PEFC certified forests.

All wood is treated with a water-based stain finish consisting of four protective coats, VOCs <100g/l.

Cylindrical base and flush pole cap, in hot dip galvanised and powder coated S235 steel.

The range is designed and developed according to eurocodes 5, standard EN40 and EN1995.

A ZEP contract for CO₂ compensation is available.



	Height (m)	Top (mm)	Base (mm)	Base Height (mm)	Door Width (mm)	Door Height (mm)	Internal Dim (mm)	Root Length (mm)
Pallas Park	4	90	140	1400	100	500	100 x 85	800
	5	90	140	1400	100	500	100 x 85	800
	6	90	140	1400	100	500	100 x 85	1000
Pallas	5	100	168	1500	100	500	100 x 85	800
	6	100	168	1500	100	500	100 x 85	1000
	7	100	193	1700	115	600	130 x 85	1200
	8	100	193	1700	115	600	130 x 85	1200

	Height (m)	Top (mm)	Base (mm)	Base Height (mm)	Door Width (mm)	Door Height (mm)	Internal Dims (mm)	Bolt Spacing (mm)	Flange Dims (mm)
Pallas Park	4	90	140	1400	100	500	100 x 85	200	270
	5	90	140	1400	100	500	100 x 85	200	270
	6	90	140	1400	100	500	100 x 85	200	270
Pallas	5	100	168	1500	100	500	100 x 85	200	270
	6	100	168	1500	100	500	100 x 85	200	270
	7	100	193	1700	115	600	130 x 85	300	400
	8	100	193	1700	115	600	130 x 85	300	400



Valmont Stainton

Dukesway, Teesside Industrial Estate
 Stockton on Tees
 TS17 9LT, United Kingdom
 T: +44 (0)1642 766242
 W: deco.valmont-stainton.com