



NOTES:

1. ALL STEEL COIL TO CONFORM TO AS/NZS 1594 GRADE HU250 UON
ALL STEEL PLATES TO CONFORM TO AS/NZS 3678 GRADE 250 UON
2. ALL STEEL BARS AND SECTIONS TO CONFORM TO AS/NZS 3679 GRADE 250 UON
3. ALL WELDS TO CONFORM TO AS/NZS 1554 PART 1
4. ALL TAPER LOCK JOINT LENGTHS ARE NOMINAL UON
5. ALL STEEL TO BE FULLY HOT DIP GALVANIZED AFTER FABRICATION
IN ACCORDANCE WITH AS/NZS 4680

REV	DATE	DESCRIPTION	BY	CHKD
3	17/08/09	PLINTH SIZE LIMITATION DETAIL 1 ADDED	I.W.	
2	24/06/09	SECTION DIMENSIONS CHANGED	C.J.	
1	13/04/05	BASEPLATE & REFERENCE DETAIL ADDED	I.W.	
0	05/02/03	UPDATED & REDRAWN FROM PL 183	P.B.	

COPYRIGHT
THIS DOCUMENT PRODUCED
BY IN GAL EPS MUST NOT
BE COPIED, TRACED,
REPRODUCED, OR LENT
WITHOUT WRITTEN CONSENT

DIMENSIONS IN MILLIMETRES

DO NOT SCALE

CHECKED BY: P.B. DATE: 09/02/03

INGAL EPS

LOWERING SYSTEMS – POWERLIFT
40m HEAVY DUTY TRACK RANGE
BASEPLATE MOUNTED
RIVERTON DESIGN

CATALOGUE NUMBER
PTH40F-W
DRAWING NUMBER
PTH40F

DATE: 05/02/03
DRAWN BY: P. BENTZEN

SCALE: 1:165
CAD FILE No.: Z:\ACAD\STD\POWERLIFT\PTH40F