



**NOTES:**

1. ALL STEEL COIL TO CONFORM TO AS/NZS 1594 GRADE HU300 U.O.N.  
ALL STEEL PLATES TO CONFORM TO AS/NZS 3678 GRADE 250 U.O.N.
2. ALL STEEL BARS AND SECTIONS TO CONFORM TO AS/NZS 3679 GRADE 250 U.O.N.
3. ALL WELDS TO CONFORM TO AS/NZS 1554 PART 1
4. ALL TAPER LOCK JOINT LENGTHS ARE NOMINAL U.O.N.
5. ALL STEEL TO BE FULLY HOT DIP GALVANIZED AFTER FABRICATION  
IN ACCORDANCE WITH AS/NZS 4680

REV	DATE	DESCRIPTION	BY	CHKD
0	24/5/02	FIRST ISSUE		

COPYRIGHT  
THIS DOCUMENT PRODUCED  
BY INGAL EPS MUST NOT  
BE COPIED, TRACED,  
REPRODUCED, OR LENT  
WITHOUT WRITTEN CONSENT

DIMENSIONS IN MILLIMETRES

DO NOT SCALE

CHECKED BY: PPA  
DATE: 30/5/02

**INGAL EPS**

LOWERING SYSTEMS – POWERLIFT  
25m MEDIUM DUTY TRACK RANGE  
BASEPLATE MOUNTED  
RIVERTON DESIGN

CATALOGUE NUMBER  
PTM25F  
DRAWING NUMBER  
PTM25F

CHECKED BY: PPA  
DATE: 30/5/02

DRAWN BY: I. WHITE  
DATE: 24/5/02

SCALE: 1:100

CAD FILE No.: Z:\ACAD\STD\POWERLIFT\PTM25F