



NOTES:

1. ALL STEEL COIL TO CONFORM TO AS/NZS 1594 GRADE HU300 U.O.N.
2. ALL STEEL PLATES TO CONFORM TO AS/NZS 3678 GRADE 250 U.O.N.
3. ALL STEEL BARS AND SECTIONS TO CONFORM TO AS/NZS 3679 GRADE 250 U.O.N.
4. ALL WELDS TO CONFORM TO AS/NZS 1554 PART 1
5. ALL TAPER LOCK JOINT LENGTHS ARE NOMINAL U.O.N.
6. ALL STEEL TO BE FULLY HOT DIP GALVANIZED AFTER FABRICATION IN ACCORDANCE WITH AS/NZS 4680

0 19/1/99 FIRST ISSUE I.W. BY CHKD A4 DO NOT SCALE 11/02/00 CHECKED BY			
REV	DATE	DESCRIPTION	BY
CUSTOMER/PROJECT			

COPYRIGHT
THIS DOCUMENT PRODUCED
BY IN GAL EPS MUST NOT
BE COPIED, TRACED,
REPRODUCED, OR LENT
WITHOUT WRITTEN CONSENT

DIMENSIONS IN MILLIMETRES

INGAL EPS

STREET LIGHTING
12m, 2m DOUBLE OUTREACH AVENUE
BASEPLATE MOUNTED
RIVERTON DESIGN

CATALOGUE NUMBER
SAL12FDO20

DRAWING NUMBER
SAL12FDO20

DATE
7/12/98

DRAWN BY
I. WHITE

SCALE
1:60

CAD FILE No.
Z:\ACAD\STD\AVENUE\SAL12F-D20