



NOTES:

1. ALL STEEL COIL TO CONFORM TO AS/NZS 1594 GRADE HU300 U.O.N.
ALL STEEL PLATES TO CONFORM TO AS/NZS 3678 GRADE 250 U.O.N.
2. ALL STEEL BARS AND SECTIONS TO CONFORM TO AS/NZS 3679 GRADE 250 U.O.N.
3. ALL WELDS TO CONFORM TO AS/NZS 1554 PART 1
4. ALL TAPER LOCK JOINT LENGTHS ARE NOMINAL U.O.N.
5. ALL STEEL TO BE FULLY HOT DIP GALVANIZED AFTER FABRICATION
IN ACCORDANCE WITH AS/NZS 4680

COPYRIGHT THIS DOCUMENT PRODUCED BY INGAL EPS MUST NOT BE COPIED, TRACED, REPRODUCED, OR LENT WITHOUT WRITTEN CONSENT				<h1>INGAL EPS</h1>	
DIMENSIONS IN MILLIMETRES 				STREET LIGHTING 9m, 3m DOUBLE OUTREACH AVENUE BASEPLATE MOUNTED RIVERTON DESIGN	
0 20/1/99 FIRST ISSUE REV DATE DESCRIPTION CUSTOMER/PROJECT		I.W. PPA BY CHKD A4 DO NOT SCALE CHECKED BY PPA DATE 23/3/99		DRAWN BY I. WHITE SCALE 1:50 CAD FILE No. Z:\ACAD\STD\AVENUE\SAL90F-D30	
				CATALOGUE NUMBER SAL9FDO30 DRAWING NUMBER SAL9FDO30	