



DOOR 295 x 110  
CLEAR OPENING  
2- CONTROL GEAR  
MOUNTING STRAPS

**NOTES:**

1. ALL STEEL COIL TO CONFORM TO AS/NZS 1594 GRADE HU300 U.O.N.  
ALL STEEL PLATES TO CONFORM TO AS/NZS 3678 GRADE 250 U.O.N.
2. ALL STEEL BARS AND SECTIONS TO CONFORM TO AS/NZS 3679 GRADE 250 U.O.N.
3. ALL WELDS TO CONFORM TO AS/NZS 1554 PART 1
4. ALL TAPER LOCK JOINT LENGTHS ARE NOMINAL U.O.N.
5. ALL STEEL TO BE FULLY HOT DIP GALVANIZED AFTER FABRICATION  
IN ACCORDANCE WITH AS/NZS 4680

REV	DATE	DESCRIPTION	BY	CHKD
0	20/1/99	FIRST ISSUE	I.W.	PBA
CUSTOMER/PROJECT				

COPYRIGHT  
THIS DOCUMENT PRODUCED  
BY INGAL EPS MUST NOT  
BE COPIED, TRACED,  
REPRODUCED, OR LENT  
WITHOUT WRITTEN CONSENT

DIMENSIONS IN MILLIMETRES

DO NOT SCALE

CHECKED BY PBA DATE 23/3/99

**INGAL EPS**

STREET LIGHTING  
9m, 3m DOUBLE OUTREACH AVENUE  
BASEPLATE MOUNTED  
RIVERTON DESIGN

CATALOGUE NUMBER  
SAL9FSO30  
DRAWING NUMBER  
SAL9FSO30

SCALE  
1:40

CAD FILE No.  
Z:\ACAD\STD\AVENUE\SAL90F-S30

DATE  
20/1/99

DRAWN BY  
I. WHITE