



NOTES:

1. ALL STEEL COIL TO CONFORM TO AS/NZS 1594 GRADE HU300 U.O.N. ALL STEEL PLATES TO CONFORM TO AS/NZS 3678 GRADE 250 U.O.N.
2. ALL STEEL BARS AND SECTIONS TO CONFORM TO AS/NZS 3679 GRADE 250 U.O.N.
3. ALL WELDS TO CONFORM TO AS/NZS 1554 PART 1
4. ALL TAPER LOCK JOINT LENGTHS ARE NOMINAL U.O.N.
5. ALL STEEL TO BE FULLY HOT DIP GALVANIZED AFTER FABRICATION IN ACCORDANCE WITH AS/NZS 4680

0	25/11/02	REDRAWN FROM SL 219 & UPDATED	P.B.	PPA
REV	DATE	DESCRIPTION	BY	CHKD
CUSTOMER/PROJECT				

COPYRIGHT
THIS DOCUMENT PRODUCED
BY INGAL EPS MUST NOT
BE COPIED, TRACED,
REPRODUCED, OR LENT
WITHOUT WRITTEN CONSENT

DIMENSIONS IN MILLIMETRES



DO NOT SCALE

INGAL EPS

STREET LIGHTING
12m, 3m DOUBLE OUTREACH FREEWAY
BASEPLATE MOUNTED
RIVERTON DESIGN

CATALOGUE NUMBER
SFL12FDO30
DRAWING NUMBER
SFL12FDO30

CHECKED BY
PPA

DATE
25/11/02

DRAWN BY
P. BENTZEN

SCALE
1:50

CAD FILE No.
Z:\ACAD\STD\FREEWAY\SFL12FDO30